

# <u>Specifications for the Hydro Model SOH-4000-CL2 Switchover Module</u> Specification SOH-4000-CL2

## 1.01 GENERAL

## 1.01.1 Completeness

The system shall be complete with all components, equipment, and appurtenances.

## 1.01.2 Quality Assurance

All materials and components shall be new and unused of first quality by well-known manufacturers. Inferior materials or components shall not be allowed.

#### 1.02 MANUFACTURER

The manufacturer shall be Hydro Instruments, Telford, PA, USA or approved equal. The switchover module shall be Hydro Instruments Model SOH-4000-CL2.

## 1.03 SPECIFICATIONS

#### 1.03.1 General

- 1. The switchover module shall be an external, mechanical device capable of automatically switching from an exhausted gas supply to a standby gas supply.
- 2. The switchover module shall have a chlorine gas feed capacity of not less than 4000 pounds per day (75 kg/hr).
- 3. The switchover module shall be constructed of materials suitable for chlorine gas under vacuum.
- 4. The vacuum connections shall be a 1.5" Schedule 80 PVC threaded Unions.

## 1.03.2 Automatic Switchover Module

- 1. The switchover module shall be suitable for wall mounting.
- 2. The switchover module body parts shall be constructed of solid machined PVC. Internal pins shall be constructed of solid silver.
- 3. The device shall operate automatically and entirely by vacuum with no need for external adjustments or reset.