



Vacuum Switchover Series 500, 200 & 700

Hydro Instruments has been manufacturing the highest quality, longest lasting and most reliable gas chlorination equipment since 1978. Our equipment is manufactured in the USA using only the highest quality materials for both chemical resistance and physical durability.

Hydro Instruments constructs its products using parts that are precision machined from the best materials for gas service.

Features

- Up to 500 PPD (10 Kg/h) Cl₂ or SO₂
Also available for Ammonia NH₃ and Carbon Dioxide CO₂
- Switchover occurs automatically and does not require to be reset or need operator interaction of any kind
- Mounting bracket for easy installation
- 3 year manufacturers warranty



Principle of Operation

Two vacuum regulators, each with an independent gas supply are connected to the gas inlets on the left and right side of the automatic switchover module. One vacuum regulator and its gas supply will be in service and the other in standby. Gas will flow through the automatic switchover module under vacuum from the in-service vacuum regulator to the flowmeter & feed rate control device until the gas supply is depleted.

The vacuum level within the vacuum regulator will then increase to a point in which the spring-loaded toggle assembly inside the automatic switchover module activates. The open port on the depleted side of the module will close and the closed port on the standby side of the module will then open to permit gas flow.

When the depleted gas supply is replaced, this gas supply and its vacuum regulator automatically becomes the standby.

Capacity & Ordering Information

Model Number	Description
SP-100	Switchover module w/ 3/8" OD tube connectors inlets & outlet 100 PPD (2 Kg/h) max.
SP-200	Switchover module w/ 1/2" OD tube connectors inlets & outlet 250 PPD (5 Kg/h) max.
SP-500	Switchover module w/ 5/8" OD tube connectors inlets & outlet 500 PPD (10 Kg/h) max.

